5

- 1. A method of manufacturing a plurality of reagent test strips, said method comprising:
- (a) providing a test strip precursor comprising an elongated support material having a first planar surface and a stripe of reagent material positioned along a central axis thereof; and
- (b) cutting said test strip precursor into a plurality of reagent test strips according to an inter-digitating pattern.
- 2. The method according to Claim 1, wherein said test strip precursor is a tape.
- 3. The method according to Claim 1, wherein said test strip precursor is a card.
- 4. The method according to Claim 1, wherein said reagent material comprises a signal producing system.
- 5. The method according to Claim 4, wherein said signal producing system produces a color that can be related to the concentration of an analyte in a sample contacted with said reagent material.
- 6. The method according to Claim 4, wherein said signal producing system produces an electrical current that can be related to the concentration of an analyte in a sample contacted with said reagent material.
- 7. The method according to Claim 1, wherein said method further comprises producing said test strip precursor.

FF-REF: Life-016

LIFESCAN REF: LFS-111

F:\DOCUMENT\life\016\patent application.doc

15

25

8. The method according to Claim 1, wherein each of said strips produced by said method includes a sample region and a handling region, where said reagent material is located in said sample region.

99 (5

9. The method according to Claim 8, wherein said sample region includes a hole in said support material which is covered by said reagent material.

5007

10. The method according to Claim 8, wherein said strip has an aspect ratio that is about 0.5.

0

11. The method according to Claim 1, wherein said test strips produced by said method can be used in a hand-held optical meter.

<u>.</u> 15

12. The method according to Claim 1, wherein said hand-held optical meter is a ONE TOUCH meter.

13. A reasent test strip produced according to the method of Claim 1, wherein said reagent test strip has a sample region and a handling region, wherein said reagent material is located in said sample region.

[] 20 [] 20

14. The reagent test strip according to Claim 13, wherein said reagent test strip has an aspect ratio of that is about 0.5.

25

15. The reagent test strip according to Claim 14, wherein said reagent test strip has a configuration that is substantially the same as or identical to a reagent test strip configuration selected from the group of configurations shown in Figures 2 to 8.



16. The reagent test strip according to Claim 15, wherein said reagent test strip can be read by a hand held optical meter.

FF-REF: Life-016

LIFESCAN REF: LFS-111

F:\DOCUMENT\life\016\patent application.doc

- The reagent test strip according to Claim 16, wherein said hand held optical meter is 17. a ONE TOUCH®
- 5 A method for determining the concentration of an analyte in a sample, said method 18. comprising:
  - applying alfluid sample to a reagent test strip of Claim 13; (a)
  - (b) detecting a signal from said reagent test strip; and
  - relating said detected signal to the concentration of analyte in said sample to (c) determine the concentration of said analyte in said fluid sample.
  - The method according to Claim 18, wherein said fluid sample is a biological sample. 19.
  - 20. The method according to Claim 18, wherein said analyte is glucose.
  - 21. The method according to Claim 18, wherein said detecting and relating steps are performed by a hand held optical meter.
  - ethod according to Claim 21, wherein said hand held optical meter is a ONE 22. TOUCH®
  - A kit for use in determining the concentration of an analyte in a physiological 23. sample, said kit comprising:
    - a reagent test strip according to Claim 13; and (a)
    - (b) at least one of:
      - (i) a means for obtaining said physiological sample; and
      - (ii) an analyte standard.

FF-REF: Life-016

LIFESCAN REF: LFS-111

F:\DOCUMENT\life\016\patent application.doc

20

10

5

- 24. The kit according to Claim 23, wherein said means for obtaining said physiological sample is a lance.
- 25. The kit according to Claim 23, wherein said analyte standard comprises a standardized concentration of a known reagent.
- 26. The kit according to Claim 23, wherein said kit comprises said means for obtaining said physiological sample and said analyte standard.
- 10 27. The kit according to Claim 23, wherein said kit further comprises a hand held optical meter.
  - 28. The ket according to Claim 27, wherein said hand held optical meter is a ONE TOUCH® meter.

FF-REF: Life-016

LIFESCAN REF: LFS-111

F:\DOCUMENT\life\016\patent application.doc